according to 1907/2006/EC, Article 31



Revision: 05.06.2012

Printing date 05.06.2012

Version number 96

1 Identification of the substance/mixture and of the company/undertaking

- · Product identifier
- · Trade name: EP-Härter 950-25
- · Relevant identified uses of the substance or mixture and uses advised against
- · Application of the substance / the preparation Hardening agent/ Curing agent
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

MIPA AG

Am Oberen Moos 1 D-84051 Essenbach Tel.: +49(0)8703-922-0 Fax.: +49(0)8703-922-100

e-mail: sdb-registratur@mipa-paints.com

www.mipa-paints.com

- · Further information obtainable from: Laboratory
- *Emergency telephone number:* +49(0)700 24112112 (MIP)

2 Hazards identification

- · Classification of the substance or mixture
- · Classification according to Directive 67/548/EEC or Directive 1999/45/EC

×

Xn; Harmful

R20/21: Harmful by inhalation and in contact with skin.

Xi; Irritant

R36/38: Irritating to eyes and skin.

R10: Flammable

· Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

· Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

- · Label elements
- · Labelling according to EU guidelines:

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

· Code letter and hazard designation of product:

Xn Harmful

· Hazard-determining components of labelling:

xylene

· Risk phrases:

10 Flammable.

20/21 Harmful by inhalation and in contact with skin.

36/38 Irritating to eyes and skin.

· Safety phrases:

2 Keep out of the reach of children.

7/9 Keep container tightly closed and in a well-ventilated place.

13 Keep away from food, drink and animal feedingstuffs.

23 Do not breathe vapour/spray.

36/37/39 Wear suitable protective clothing, gloves and eye/face protection.

(Contd. on page 2)

according to 1907/2006/EC, Article 31



Printing date 05.06.2012 Version number 96 Revision: 05.06.2012

Trade name: EP-Härter 950-25

(Contd. of page 1)

46 If swallowed, seek medical advice immediately and show this container or label.

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous compone	ents:	
CAS: 160901-21-3	4,4`-Isopropylidendiphenol-1-chloro- 2,3-epoxypropan-Cooligomeren Xi R36/38 ◆ Skin Irrit. 2, H315; Eye Irrit. 2, H319	50-100%
CAS: 1330-20-7 EINECS: 215-535-7	xylene Xn R20/21; Xi R38 R10 ♦ Flam. Liq. 3, H226; ♦ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	25-50%
CAS: 71-36-3 EINECS: 200-751-6	butan-1-ol Xn R22; Xi R37/38-41 R10-67 → Flam. Liq. 3, H226; → Eye Dam. 1, H318; → Acute Tox. 4, H302; Skin Irrit. 2, H315; STOT SE 3, H335+H336	2.5-10%

[·] Additional information: For the wording of the listed risk phrases refer to section 16.

4 First aid measures

- · Description of first aid measures
- · General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Firefighting measures

- · Extinguishing media
- · Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture No further relevant information available.

(Contd. on page 3)

according to 1907/2006/EC, Article 31



Printing date 05.06.2012 Version number 96 Revision: 05.06.2012

Trade name: EP-Härter 950-25

(Contd. of page 2)

· Advice for firefighters

· Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Store away from foodstuffs.
- · Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 3
- \cdot *Specific end use*(s) *No further relevant information available.*

8 Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · Control parameters

	Ingrad	lionte	with	limit	values	that	roaniro	monito	rina a	t the	workpla	co.
•	· Ingreu	uenis	wiiii	umu	vaiues	ınuı	reuune	manua	ıını u	ıınıe	working	Le.

1330-20-7 xylene

WEL () Short-term value: 441 mg/m³, 100 ppm Long-term value: 220 mg/m³, 50 ppm Sk; BMGV

71-36-3 butan-1-ol

WEL () Short-term value: 154 mg/m³, 50 ppm Sk

· Additional information: The lists valid during the making were used as basis.

(Contd. on page 4)

according to 1907/2006/EC, Article 31



Printing date 05.06.2012 Version number 96 Revision: 05.06.2012

Trade name: EP-Härter 950-25

(Contd. of page 3)

- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Protection of hands:

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

- · Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Fluid

Colour: According to product specification

Odour: CharacteristicOdour threshold: Not determined.

· pH-value: Not determined.

· Change in condition

Melting point/Melting range: Undetermined.
Boiling point/Boiling range: 116°C

• Flash point: 27°C (DIN 53213)

· Flammability (solid, gaseous): Not applicable.

(Contd. on page 5)

Safety data sheet according to 1907/2006/EC, Article 31



Printing date 05.06.2012 Version number 96 Revision: 05.06.2012

Trade name: EP-Härter 950-25

	(Contd. of page 4
· Ignition temperature:	340°C (DIN 51794)
· Decomposition temperature:	Not determined.
· Self-igniting:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air, vapour mixtures are possible.
· Explosion limits:	
Lower:	1.1 Vol %
Upper:	7.0 Vol %
· Vapour pressure at 20°C:	6.7 hPa
Density at 20°C:	0.941 g/cm³ (DIN 53217)
Relative density	Not determined.
· Vapour density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
· Segregation coefficient (n-octanol/v	water): Not determined.
· Viscosity:	
Dynamic at 20°C:	1500 mPas
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	40.0 %
VOC (EC)	376.3 g/l
Solids content (weight-%):	60.0 %
Other information	No further relevant information available.

10 Stability and reactivity

- · Reactivity
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: Carbon monoxide

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

· LD/LC50 values relevant for classification:					
1330-20-7	1330-20-7 xylene				
Oral	LD50	8700 mg/kg (rat)			
Dermal	LD50	2000 mg/kg (rabbit)			
Inhalative	LC50/4 h	15 mg/l (rat)			

- · Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.

(Contd. on page 6)

according to 1907/2006/EC, Article 31



Printing date 05.06.2012 Version number 96 Revision: 05.06.2012

Trade name: EP-Härter 950-25

(Contd. of page 5)

- · on the eye: Irritating effect.
- · Sensitization: No sensitizing effects known.
- $\cdot \textit{Additional toxicological information:}$

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Harmful Irritant

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behaviour in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

08 01 11* waste paint and varnish containing organic solvents or other dangerous substances

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

4	Trans	port	in	formai	tion
		, , ,	,	Q	

	UN-Number
--	-----------

· ADR, IMDG, IATA UN1263

· UN proper shipping name

· ADR 1263 PAINT RELATED MATERIAL, special provision 640E

· IMDG, IATA PAINT RELATED MATERIAL

(Contd. on page 7)

GB ·

according to 1907/2006/EC, Article 31



Printing date 05.06.2012 Version number 96 Revision: 05.06.2012

Trade name: EP-Härter 950-25

(Contd. of page 6)

· Transport hazard class(es)

 $\cdot ADR$



· Class 3 (F1) Flammable liquids.

· Label

· IMDG, IATA



· Class 3 Flammable liquids.

· Label

· Packing group

· ADR, IMDG, IATA III

· Environmental hazards:

· Marine pollutant: No

· Special precautions for user Warning: Flammable liquids.

Danger code (Kemler): 30EMS Number: F-E,S-E

· Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code Not applicable.

· Transport/Additional information:

 $\cdot ADR$

• Tunnel restriction code
 • Remarks:
 D/E
 • ≤ 450 l: -

· IMDG

• Remarks: $\leq 30 l$:

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · National regulations:
- · Information about limitation of use:

None of the ingredients is listed.

Class	Share in %
NK	25-50

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

(Contd. on page 8)

Safety data sheet according to 1907/2006/EC, Article 31



Printing date 05.06.2012 Version number 96 Revision: 05.06.2012

Trade name: EP-Härter 950-25

(Contd. of page 7)

•	Rel	levant	phi	ases
---	-----	--------	-----	------

- H226 Flammable liquid and vapour.
- H302 Harmful if swallowed.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- R10 Flammable.
- R20/21 Harmful by inhalation and in contact with skin.
- Harmful if swallowed.
- R36/38 Irritating to eyes and skin.
- R37/38 Irritating to respiratory system and skin.
- R38 Irritating to skin.
- R41 Risk of serious damage to eyes.
- R67 Vapours may cause drowsiness and dizziness.
- · Department issuing MSDS: APP Auto-Plast Produkt Sp.z o.o
- · Contact: Rafal Roguszka
- * * Data compared to the previous version altered.